

# THOOSA 5500

The Thoosa 5500 is a 5.5kW - 48V system. The system uses a permanent magnet motor mounted on a stainless steel gearing frame that is controlled by a 4-quadrant motor drive.

## CHARACTERISTICS

### Increased reliability

An electric motor starts every time.

### Power immediately available

No need for pre-heating – the power is immediately available.

### Low weight:

The weight of the electric system is very low – and batteries can be distributed for better weight optimization.

### Low maintenance costs:

The only maintenance parts in the system are the brushes and the gearbelt.

### Easy installation:

Low weight of the motor and gearing, and a motor controller designed for easy installation.



## Electric Inboard Drive Systems

5500 W continuous power

Replaces 11-18 hp internal combustion engines

## RECOMMENDED USE

The Thoosa 5500 is engineered for boats 18' - 26'

## SECURITY AND COMFORT

An electric motor starts every time - just turn the key, adjust the throttle and GO. With our electric motor, the power kicks in immediately, making harbor maneuvering easier and more accurate.

The system is virtually silent and allows people on deck to speak with each other while maneuvering in harbors, making the event enjoyable, safer and relaxing.

The low weight of the electric motor solution also improves the maneuvering abilities of the boat since the heaviest part of the system (the batteries) can be moved into e.g. the keel.

## ENVIRONMENT AND COMFORT

Not only does an electric motor solution free the harbor and sea from oil spills, it also frees you from the smell of diesel and exhaust fumes, providing you with a clean engine room, making the onboard environment more pleasant.

## INSTALLATION

Due to the motor and gearing console's low weight, the motor is easy to align without the need for heavy tools.

The motor controller is designed for easy installation so throttle, key-lock, charger, battery monitor and DC-DC converter can be connected by "plug and sail".

## MAINTENANCE

The cost of maintenance is very low since it is only needed for two parts.

The brushes have a lifetime of 4000 hours.

The gear belt has a life time of 3000 hours.

Both parts are easy to replace.

## FUNCTIONALITY & EFFICIENCY

The electric motor has a stationary magnetic field (stator) and a rotating magnetic field (rotor) that either attracts or repels each other and thereby creates rotation.

Where an "ordinary" DC motor uses standard magnets and a cylindrical rotor, the motor in the Thoosa 5500 system uses double the neodymium magnets and a disc shaped rotor. This makes the motor very powerful and very efficient.

The rpm on the motor are regulated by adjusting the voltage with the motor controller. The motor controller chops the voltage from the batteries into small pulses. The longer the pulses it sends to the motor, the more power and rpm are provided by the motor. This makes the system more efficient.

## POWER CHARACTERISTICS

An internal combustion engine idles at 700-800 rpm – and must rotate at 1500- 2000 rpm to make enough torque to drive the boat forward.

Our electric system does not idle and provides full torque at any speed if it runs at full current. This gives you have a very high torque available for acceleration.

The main power consumption is used to accelerate the boat up to the desired speed. Thereafter, the power consumption drops significantly when using an electric motor.

All in all, this shows that an electric motor solution is a feasible and efficient alternative to a combustion engine.

## REGENERATION: CHARGING BATTERIES WHILE SAILING

By RG the motor works as a generator and sends a positive charge to the battery bank, while the boat is driven by wind/sails. What is achieved through regeneration is supplemental, much as you would receive from wind or solar. For more information on regeneration speak with your dealer.



US Distributor - Annapolis Hybrid Marine  
311C Thrid St. Annapolis, MD 21403  
info@annapolishybridmarine.com  
www.annapolishybridmarine.com

## Thoosa 5500

### Technical data



#### CUSTOMER SERVICE

Standard design proposal for the specific boat is always included in our offer, free of charge.

If you have special mechanical or electrical requirements to any of our THOOSA systems, please contact us for further information.

#### Technical data

Motor type:	SAIETTA 199/199R
Voltage	48V DC
Current:	140 Amp (limited by motor controller)
Power output:	5.5 KW
Average efficiency:	93%
Battery regeneration:	Yes
Rated speed engine:	3,264 rpm
Rated torque:	16.2 Nm
Speed constant:	68 rpm/V
Peak current:	300 Amp (instantaneous)
Peak Power:	13.2 KW (instantaneous)
Peak torque:	35,4 NM (instantaneous)

Reduction:	AM D/02
Standard gearing:	22:48 wheel combination
Gear Belt:	600 / 624 / 656
Standard Rpm propeller shaft:	1560 Rpm
Option Rpm propeller shaft:	1335 Rpm
Option Rpm propeller shaft:	1040 Rpm

Weight of motor and console:	21 kilo
Weight of Thoosa5500 system:	35 kilo
Recommended boat size:	15-26 feet

#### THOOSA 5500 System



Motor, included console, with reduction and mounting brackets



Motor Controller



Key Switch System

#### ADDITIONAL SYSTEM COMPONENTS



#### THROTTLES

Dual top mounted throttles for twin engine applications

Included in system



Side mounted throttle - can be mounted port or starboard

Included in system



#### BATTERY MONITOR

Standard battery monitor  
Other monitors are available